




Prevention Technologies, Inc.

PTi Twin Tube Paste:



PTi Twin Tube Paste

Twin 20 oz. tubes

Available in:

3-pack

6-pack

48-pack

Uses:

Sealant / Caulking

Boot Repair



Twin Tube Gun

Available in:

Manual operated

Air operated

Uses:

Mix & dispense PTi

Twin Tube Paste

Description:

PTi Twin Tube Paste is an effective sealer for concrete seams and cracks. Due to its high polysulfide polymer content, it is resistant to many chemicals, shrinkage, aging, thermal stress and the effects of outdoor exposure. It's excellent adhesion and flexibility makes it a great choice in areas where petroleum and chemical resistance is needed. PTi Twin Tube Paste is also resistant to all hydrocarbon fuel components.

Recommended Uses:

PTi Twin Tube Paste is intended for use in concrete expansion joints, both indoors and outdoors. It resists the effects of sunlight, rain, snow, ozone, aging, shrinkage and daily and seasonal cyclic changes of temperature, even after years of service.

A common use of PTi Twin Tube Paste is the sealing of joints in concrete in gasoline service stations. The PTi Twin Tube Paste is simply inserted into a Twin Tube Gun and affixed with a mixing nozzle to begin the simple installation.



The joint is then filled to about 1/2-inch depth and smoothed, if desired for aesthetic appearance. The result is a good-looking seam that is fully fuel compatible, and it will last for many years.



Limitations:

The PTi Twin Tube Paste must be stored in a horizontal position. It is not recommended for use below 40°F or above 95°F. Store in a dry place at temperatures between 65 and 80°F. Substrate temperature must be at least 5°F above the dew point.